

JALNAYAK

0.5 HP and 1.0 HP MINI SERIES PUMP



Overhead tanks in bungalows



Domestic water supply



Feed water to RO plants



rater Constructio lants sites



Lawn sprinklers



Gardens & fountains



Car washing

24 MONTHS WARRANTY

'F'CLASS Insulation

> Aluminum Die Cast Motor Body



JALNAYAK - I (1.0 HP)



(0.5 HP)

JALNAYAK - II



Robust Construction



CED Coating

Superior resistance against corrosion



Wide Voltage Range

Protection against voltage fluctuations from 180 to 260 volts



Thermal Overload Protector (TOP)

Protects the motor from overloading and prevents the motor from burning



Enhanced Safety Features

Covered electrical parts offer additional safety

Always buy pumps with



and



logos on packaging



JALNAYAK

0.5 HP and 1.0 HP MINI SERIES PUMP

Applications

- > Water supply to overhead tanks in bungalows
- Feed water to RO Plants
- Construction sites
- Gardens and fountains
- > Car Washing

- Domestic Water Supply
- > Lawn sprinklers

Features

- ➤ **High Efficiency and Energy Saving Design:** Innovative design manufactured at state of art plant, delivers optimum efficiency at lower energy consumption resulting in significant cost savings.
- > **High Grade F Class Insulation:** Robust design to withstand higher temperatures reducing the chances of motor burning and ensures the reliability, safety and enhanced life.
- ➤ Thermal Overload Protector (TOP): The pump set features a Thermal Overload protector that protects the motor from overloading, shielding the motor and associated circuit from the effects of fault current.
- Cathodic Electro Deposition (CED) Coating: CED is the latest coating technology for corrosion resistance with uniform coating, provides 5 times more protection over conventional painting, resulting in longer life. Hydraulic parts of Kirloskar pumps are CED coated.
- > Wide Voltage Range: The motor is designed to withstand wide voltage fluctuations from 180 to 260 volts (Single Phase) / 300 to 440 Volts (Three Phase) and reduces chances of motor burning due to low/high voltage.
- > Shielded Ball Bearing: The pumps are fitted with shielded ball bearings, which results in low noise level and so no external lubrication is required throughout the life cycle.
- > **Dynamically Balanced Rotating Parts:** Minimum vibrations protect components from damages during the operations, consistent performance as concentricity is maintained.
- > Easy Maintainable Designs: Easy maintainable design and better interchangeability of components so that pump can be serviced even at remote locations by semi-skilled technicians.
- ➤ **High Suction Lift:** The pump has suction lift capacity up to 7.5 meters with high head, allowing to pump water at high volumes for a variety of applications.
- ➤ Enhanced Safety Features: All electrical parts of the pump are covered, which makes it safer to use.

Technical Specifications

Model	Jalnayak - II (Gold)	Jalnayak - I (Gold)
Head Range	6-30m	6-48m
Capacity Range	2650 to 660 (LPH)	4050 to 1040 (LPH)
Power Rating	0.37 kW/0.5 (HP)	0.75 kW/1.0 (HP)
Phase	Single / Three	Single / Three
Voltage Range	180-260 Volts (Single Phase) / 300 – 440 Volts (Three Phase)	180-260 Volts (Single Phase) / 300 – 440 Volts (Three Phase)
Insulation	'F' Class	'F' Class

Material of Construction

Impeller : Brass

Delivery Casing : Cast Iron

Motor Body : Aluminum Die Cast

Shaft : Carbon Steel

Mechanical Seal : Carbon Vs. Ceramic

Performance under standard conditions

Pump Model	Power Rating		Pipe Size (mm)		Rated Voltage	TOTAL HEAD IN METERS																
	kW	НР	Suc.	Del.	(Single/ Three Phase)	6	10	12	14	18	20	22	24	26	28	30	32	34	38	40	42	48
						DISCHARGE IN LPH																
JALNAYAK-II (GOLD)	0.37	0.5	25	25	220/415	2650	2300	2160	1980	1650	1470	1330	1150	970	820	660						
JALNAYAK-I (GOLD)	0.75	1	25	25	230/415	4050	3745	3600	3455	3165	3025	2880	2735	2590	2445	2300	2160	2015	1725	1580	1440	1040

KIRLOSKAR BROTHERS LIMITED

A Kirloskar Group Company

Registered Office & Global Headquarters: "Yamuna", Survey No. 98/(3 to7), Plot No. 3, Baner, Pune - 411 045, Maharashtra, India Tel: +91(20)27214444, Email: marketing@kbl.co.in, Website: www.kirloskarpumps.com CIN No.: L29113PN1920PLC000670

