



Enriching Lives



CHHOTU

COMPACT,
MULTI-PURPOSE
PUMP FOR DOMESTIC
APPLICATION



STRENGTHENED BY
99.9%
PURE EC GRADE
COPPER WINDING WIRES

BUY ELECTRIC PUMPS WITH PURE COPPER WINDING WIRES ONLY. ENQUIRE BEFORE BUYING.

ALWAYS BUY PUMPS WITH



and



LOGOS ON PACKAGING

CHHOTU

0.5 HP MINI PUMP

TECHNICAL SPECIFICATION

Head Range	- 6 to 26 Meters
Capacity Range	- 1980 to 360 LPH
Power Rating	- 0.37 kW / 0.5 HP
Phase	- Single
Voltage Range	- 180 to 240 Volts

APPLICATIONS

- Water supply to over head tanks in bungalows
- Gardens/ fountains
- Feed water to RO plants
- Domestic water supply
- Construction site
- Home pressure boosting
- Car Washing
- Lawn sprinklers

FEATURES

High Suction Lift

The pump has suction lift capacity of up to 7.5 metres with high head, facilitating pumping of water at high volumes for a variety of applications.

Cathodic Electro Deposition (CED) Coating

CED is the latest coating technology for corrosion resistance with a uniform coating. It provides 5 times more protection over conventional painting, resulting in longer life. All major CI parts of Kirloskar pumps coming in contact with the water are CED coated.

TOP - Thermal Overload Protector

The pump set features a Thermal Overload Protector that protects the motor from overloading, shielding of the motor and associated circuit from the effects of fault current

Handle to Enhance Grip and Portability

A handle attached to the pump allows user to carry the pump anywhere, adding to its portability and convenience of use.

Easy Maintainable Designs

Easy maintainable design and better interchangeability of components ensures that the pump can be serviced even at remote locations by semi-skilled technicians.

Shielded Ball Bearing

The low noise pumps are fitted with shielded ball bearing; so, no external lubrication is required throughout the life cycle.

High Efficiency and Energy Saving Design

Innovative design manufactured at state of the art, plant ensures optimum efficiency and lower energy consumption resulting in significant cost savings.

Dynamically Balanced Rotating Parts

Minimum vibration protect components from damage during the operation, thus ensuring consistent performance as concentricity is maintained.

PERFORMANCE CHART OF CHHOTU MINI RANGE PUMP, AT RATED VOLTAGE, 50Hz FREQUENCY, SINGLE PHASE A.C. POWER SUPPLY

S. No.	Pump Model	Power Rating		Pipe Size (mm)		Current (Amps)	Rated Voltage (Volts)	TOTAL HEAD IN METERS					
		kW	HP	SUC.	DEL			6	10	14	18	22	26
								DISCHARGE IN LPH					
1	CHHOTU	0.37	0.5	25	25	2	220	1980	1620	1296	1008	702	360

Note:

- Performance under standard test conditions and may vary on site conditions.
- Performance applicable to liquid of specific gravity 1 and viscosity as of water.

KIRLOSKAR BROTHERS LIMITED

Established 1888

A Kirloskar Group Company



We are now on WhatsApp to assist you better

9922710710

Toll Free Number: 1800 123 4443

www.kirloskarpumps.com

Registered Office & Global Headquarters: "Yamuna", Survey No. 98/(3 to7), Plot No. 3, Baner, Pune - 411 045, Maharashtra, India

Email: marketing@kbl.co.in, Website: www.kirloskarpumps.com CIN No.: L29113PN1920PLC000670